

Purpose:

This document lists the key specifications for compatible, 200-GHz, Dense Wavelength Division Multiplexing (DWDM) modules, which are offered by Cisco and by Fiberdyne Labs. The Cisco specifications were current (i.e. available on their website), as of January 2003.

Summary:

The following is a summary of specific differences between compatible units. Fiberdyne modules perform as well as Cisco's products -- or better. Fiberdyne offers these products at a significant cost savings. Additionally, Fiberdyne offers **flexibility** – port configuration/number, wavelength selection, etc.

Modules can be customized according to customer requirements/needs. Purchase only those channels, which you need, now. Then, when more channels are required, buy Fiberdyne upgrade modules. Do you want specific monitoring capabilities? Do you need a mix of 1310/1550 WDM, Coarse WDM and DWDM? Fiberdyne offers a wide array of packaging, port-count, channel and other configuration options.

Fiberdyne platforms also offer:

- Lower end-to-end insertion loss.
- Larger passband.
- Improved channel uniformity.
- Better passband flatness.
- Higher return loss.

On the subsequent pages, you will find the full, parameter-for-parameter comparison. If you have any questions, please contact Fiberdyne Labs.

*Fiberdyne Labs
127 Business Park Dr.
Frankfort, NY 13340
1-800-894-9694*

Mux/Demux Modules

Item Description	Unit	Cisco® ONS 15216		Fiberdyne FD15216-200	
Channel Spacing	GHz	200		200	
Center Wavelength per Channel	nm	Base (Red) Unit	Upgrade (Blue) Unit	Base (Red) Unit	Upgrade (Blue) Unit
		1547.72	1530.33	1547.72	1530.33
		1549.32	1531.90	1549.32	1531.90
		1550.92	1533.47	1550.92	1533.47
		1552.52	1535.04	1552.52	1535.04
		1554.13	1536.61	1554.13	1536.61
		1555.75	1538.19	1555.75	1538.19
		1557.36	1539.77	1557.36	1539.77
		1558.98	1541.35	1558.98	1541.35
		1560.61	1542.94	1560.61	1542.94
End-to-end Insertion Loss, mux+demux	dB	< 9		< 7	
Channel Uniformity	dB	< 2.0		< 1.5	
Filter Passband @ -0.5 dB	nm			> 0.6	
Passband flatness	dB			< 0.5	
Isolation of dropped channels: - adjacent channels		> 25		> 25	
- non-adjacent channels	dB	> 40		> 40	
Polarization dependent loss	dB			< 0.2	
Polarization mode dispersion	ps	< 0.1		< 0.1	
Chromatic Dispersion	ps	< 10			
Directivity	dB	> 35		> 50	
Return Loss	dB	> 40		> 45	
Insertion Loss of monitor ports - Multiplexer (1% tap) - Demultiplexer (5% tap)	dB	< 26.0 < 14.6		< 24.8 < 13.4	
Input Optical Power	mW	< 250		< 250	
Temperature – Operating	°C	0 to 70		0 to 70	
Temperature – Storage	°C	-40 to +85		-40 to +85	
Connectors		SC/UPC		SC/UPC	
Dimensions	inch	1.75 x 17.4 x 11		1.75 x 17.4 x 8.5 *	

* Note: module depth (8.5 inch) does not include fiber management shelf.

Depth is 11 inches, with fiber management shelf.

Fiberdyne 200-GHz (Mux/Demux) PLATFORM versus Cisco™ ONS 15216 DWDM 200-GHz Filter Solution	Fiberdyne Labs, Inc. Product Comparison
--	--

Optical Add/Drop Modules (OADM): 1-channel

<i>Item Description</i>	<i>Unit</i>	<i>Cisco® ONS 15216</i>	<i>Fiberdyne FD15216-200</i>
Channel Spacing	GHz	200	200
Number of wavelengths	#	16	16
Wavelength Tolerance	nm	+/- 0.25	+/- 0.3
Filter Passband @ -1 dB	nm	+/- 0.25	+/- 0.3
End-to-end Insertion Loss, mux+demux	dB	< 1.8 pass < 2.1 drop < 3.2 add	< 1.4 pass < 1.6 drop < 3.0 add
Passband flatness	dB	< 1.0	< 0.5
Isolation of dropped channels: - adjacent channels - non-adjacent channels	dB	> 30 > 40	> 30 > 40
Polarization mode dispersion	ps	< 0.1	< 0.1
Directivity	dB	> 55	> 50
Return Loss	dB	> 40	> 40
Connectors		SC/UPC	SC/UPC
Temperature – Operating	°C	0 to 70	0 to 70
Temperature – Storage	°C	-40 to +85	-40 to +85
Dimensions	inch	1.75 x 17.4 x 11	1.75 x 17.4 x 8.5 *

* Note: module depth (8.5 inch) does not include fiber management shelf.
Depth is 11 inches, with fiber management shelf.

Optical Add/Drop Modules (OADM): 2-channel

<i>Item Description</i>	<i>Unit</i>	<i>Cisco® ONS 15216</i>	<i>Fiberdyne FD15216-200</i>
Channel Spacing	GHz	200	200
Number of wavelength combinations	#	8	flexible
Wavelength Tolerance	nm	+/- 0.25	+/- 0.3
Filter Passband @ -1 dB	nm	+/- 0.25	+/- 0.3
End-to-end Insertion Loss, mux+demux	dB	< 2.0 pass < 2.6 drop < 4.0 add	< 1.5 pass < 2.1 drop < 3.5 add
Passband flatness	dB	< 1.0	< 0.5
Isolation of dropped channels: - adjacent channels - non-adjacent channels	dB	> 30 > 40	> 30 > 40
Polarization mode dispersion	ps	< 0.1	< 0.1
Directivity	dB	> 55	> 50
Return Loss	dB	> 40	> 40
Connectors		SC/UPC	SC/UPC
Temperature – Operating	°C	0 to 70	0 to 70
Temperature – Storage	°C	-40 to +85	-40 to +85
Dimensions	inch	1.75 x 17.4 x 11	1.75 x 17.4 x 8.5 *

* Note: module depth (8.5 inch) does not include fiber management shelf.
Depth is 11 inches, with fiber management shelf.