FIBERDYNE TERMINATION BOX PART NUMBER INFORMATION

FB __ __ __ __ __ __ __ __ __ __ __ *
a b c d e f g h i j k

a. **BOX MANUFACTURER**

1=CORNING	3=OFS	5=CS-SYSTIMAX
2=AMP	4=FIBERDYNE LABS	

b. **BOX TYPE**

1=WALL MOUNT	3=CABINET MOUNT	L= CTM-072 (Fiberdyne L Bracket)
2=RACK MOUNT	4=1U HIGH RACK MOUNT	
E=ENVIRONMENTAL (WALL/POLE MOUNT)	5=2U HIGH RACK MOUNT	

c. **CAPACITY**

1=12 PORT	5=96 PORT
2=24 PORT	6=144 PORT
3=48 PORT	7=36 PORT
4=72 PORT	8=288 PORT

d. **FIBER TYPE**

A1=SINGLEMODE	C1=MULTIMODE 50/125	X1=HYBRID CONFIGURATION
B2=MULTIMODE 62.5/125	Q1=MULTIMODE 50/125 AQUA	00=NO FIBER

e. **ADAPTER; MATING SLEEVE; INTERCONNECT SLEEVE**

0=NO PANELS	D=E2000/APC	R=MTRJ (WITH PINS)
1=ST	E=E2000/PC	S=DUPLEX ST
2=FDDI	F=LC/APC DUPLEX	T=MTP/APC (NO PINS)
6=SC/PC	G=QUAD LC (SC DUPLEX FOOTPRINT)	U=MU
7=FC/PC	H=MTP/APC (WITH PINS)	W=SC/APC DUPLEX
8=ESCON	M=MTRJ (NO PINS)	X=CUSTOM CONFIGURATION
A=FC/APC	N=LC/APC	Y=DUPLEX SC
B=SC/APC	P=MTP (WITHOUT PINS)	Z=BLANK PANELS
C= LC DUPLEX	Q=MTP (WITH PINS)	

f. **SPLICE CAPACITY**

0=NONE
1=FUSION SPLICING

g. **CABLE OPTION**

0=NONE	3=MULTIPLE FIBER PIGTAIL
1=INDIVIDUAL 900UM PIGTAILS	4=MULTIPLE FIBER JUMPER
2=INDIVIDUAL JACKETED PIGTAILS (*specify 1.6, 2MM or 3MM)	X=CUSTOM CONFIGURATION

h , i , j, k **FIBER PIGTAILS**

0000=NONE
__ __ __=LENGTH FOLLOWED BY "M"(METERS) OR "F"(FEET)

* **ADDITIONAL INFORMATION**

EX:
PE=PULLING EYE
PARTIALLY LOADED TO xx FIBER COUNT
JACKETED PIGTAIL SIZE