

3Com™ Compliant Ethernet Transceiver 1000Base-LX

[Back to SFP Page](#)

3CSFP92:	FDN-3CSFP92
3Com™ Compliant Ethernet Transceiver	
1.25GB Gigabit Ethernet / 1.063GB Fiber Channel	
<p>Application: This 100% 3Com™ Compliant 1000Base LX SFP Transceiver is hot-swappable and designed to plug directly into your SFP/Mini-GBIC interface slot in your router and switch for Ethernet and Fiber Channel network interface applications.</p>	
Reach	10km
Fiber Type	SM Singlemode Fiber
Fiber Optic Connector	LC
Center Wavelength	1310nm
Min TX Power	-9.5 dBm
Max TX Power	-3 dBm
RX Sensitivity	-20 dBm
Max Input Power	-3 dBm
Link Budget	10.50 dB
Dimensions	MSA SFP Standard Height: 0.33" (8.5 mm) Width: 0.52" (13.4 mm) Depth: 2.18" (55.5 mm)
Power	3.3V
Operating Temperature	0°C - 70°C
Standards	IEEE: 802.3 2003; ANSI X3.297-1997
Compliance	IEC-60825; FDA-21; CFR 1040.10 CFR 1040.11
Warranty	1 Year Full Replacement