

50/125 OM2 Multimode Simplex Pigtail 900µm

Other Connector Combinations Available

Color coded [6 pack & 12 pack pigtails](#) available

[2 & 3mm cables available](#)



LC with Black Boot

Cable & Connector Specifications:	
Fiber Type	50/125 OM2 Multimode
Insertion Loss Per Connector	< 0.3dB, Typical 0.25dB
Return Loss VS. Polish Type	UPC: > 50dB, Typical 55dB APC: > 60dB, Typical 65dB
Apex Offset	< 50µm
Fiber Height	< 100nm
Repeatability	> 500 Cycles
Operating Temperature	-40°C To +75°C
Humidity Range	5% To 95% (Non-Condensing)
Strain Relief Boot Lengths	2.2cm to 3.5cm Available

50/125 OM2 Multimode Simplex Pigtail 900um		
LC-Pigtail Simplex	F9G1BC4GCL0XXX	Specify Length When Ordering
SC-Pigtail Simplex	F9G1BC4GC60XXX	Specify Length When Ordering
FC-Pigtail Simplex	F9G1BC4GC70XXX	Specify Length When Ordering
ST-Pigtail Simplex	F9G1BC4GC10XXX	Specify Length When Ordering

Other Connector Combinations available.