

62.5/125 OM1 Corning Multimode Simplex Riser 2.0mm Jacket

Custom Labeling Available

Other Connector Combinations Available

Boot Options:

- - Short boots
- - Bendable Boots
- - *45° Boots
- - *90° Boots

Plenum cable available upon request

3mm cables available

***Not available on all boots**



Simplex LC

Cable & Connector Specifications:	
Fiber Type	62.5/125 OM1 Multimode
Insertion Loss Per Connector	<0.4dB, Typical 0.25dB
Fiber Height	< 100nm
Repeatability	> 500 Cycles
Operating Temperature	-40°C To +75°C
Humidity Range	5% to 95% (Non-Condensing)
Strain Relief Boot Lengths	3cm to 5cm Available
Standard Compliance	Telcordia

62.5/125 OM1 Corning Multimode Simplex Riser 2.0mm Jacket		
LC-LC Simplex	F1C11B4SCLLXXX	Specify Length When Ordering
LC-SC Simplex	F1C11B4SCL6XXX	Specify Length When Ordering
SC-SC Simplex	F1C11B4SC66XXX	Specify Length When Ordering
SC-ST Simplex	F1C11B4SC61XXX	Specify Length When Ordering
ST-ST Simplex	F1C11B4SC11XXX	Specify Length When Ordering

Other Connector Combinations available.