

F	S	C	-	X	X	X	-	X	X	X	-	X	X	X
				4	5	6		7	8	9		10	11	12
FSC = Fiberdyne Labs Single Window Splitters/Couplers														

4 th Digit	Center Wavelength	0 = 1550 nm 2 = 1310 nm
5 th Digit	Ports	1 = 1x2 2 = 2x2
6 th Digit	Package	0 = 250µm 0.13" x 2.2" 1 = 900µm 0.13" x 2.2" Y = Y Cable (1x2, 3mm, 1 Meter Overall Length) Heavy Duty (H.D.) Case = 4" x 0.6" x 0.3" 2 = H.D. Case w/3mm Legs 3 = H.D. Case w/2mm Legs 4 = H.D. Case w/Outdoor Rated 2mm Legs B = H.D Case w/900µm Legs
7 th Digit	Grade	0 = Exact 1 = Premium 2 = Standard Not Available
8 th & 9 th Digits	Split Ratio	Specify First Two Digits <i>i.e.</i> 76 = 76/24 50 = 50/50
10 th Digit	Fiber Type	0 = Corning® SMF-28e+®
11 th Digit	Connector Type	0 = None 1 = FC 2 = FC/APC 3 = SC 4 = SC/APC 5 = ST 6 = D4 7 = Other (Specify) 8 = Custom Configuration (Specify) (<i>i.e.</i> LC input to SC/APC outputs) L = LC/UPC N = LC/APC
12 th Digit	Overall Length	1 = 1 Meter (0.5 meter input, 0.5 meter output) 2 = 2 Meters (1 meter input, 1 meter output)