


Introduction:

Fiberdyne Labs Inc. Multimode Pigtail Style 900µm Preconnectorized Multiple Fiber Backbone Cable Assemblies are available with pulling eyes that are flexible enough to be pulled through conduit.

- Multimode 62.5 (OM3 and OM4 Available)
- 900µm Breakout
- SC Connectors Standard.
Call for other connector types.
- Pulling eyes available to facilitate installation. [Removal Instructions](#)
- **Call with Custom Requirements**
(ie. Installed in Innerduct)



Breakout Colors



Multi-Fiber Drawing



Pulling Eye



Multimode Pigtail Style 900mm Breakout

Multimode 62.5, 900µm Micron Pigtail Style Preconnectorized

Fiber Count	Indoor Riser	Indoor Plenum	Indoor/Outdoor Tight Buffered Distribution	Outdoor Dielectric	Outdoor Armored
4	F9G51B2GC60XXF	F9G52B2GC60XXF	F9G53B2GC60XXF	Call for Information	Call for Information

900µm Breakout

SC Connectors Standard.

Pulling eyes available to facilitate installation.

Call with Custom Requirements (ie. Installed in Innerduct)

Multimode 62.5, 900µm Micron Pigtail Style Preconnectorized

Fiber Count	Indoor Riser	Indoor Plenum	Indoor/Outdoor Tight Buffered Distribution	Outdoor Dielectric	Outdoor Armored
6	F9G61B2GC60XXF	F9G62B2GC60XXF	F9G63B2GC60XXF	F9G64B2GC60XXF	F9G65B2GC60XXF

900µm Breakout

SC Connectors Standard.

Pulling eyes available to facilitate installation.

Call with Custom Requirements (ie. Installed in Innerduct)

Multimode 62.5, 900µm Micron Pigtail Style Preconnectorized

Fiber Count	Indoor Riser	Indoor Plenum	Indoor/Outdoor Tight Buffered Distribution	Outdoor Dielectric	Outdoor Armored
8	F9G71B2GC60XXF	F9G72B2GC60XXF	Call for Information	Call for Information	Call for Information

900µm Breakout

SC Connectors Standard.

Pulling eyes available to facilitate installation.

Call with Custom Requirements (ie. Installed in Innerduct)

Multimode 62.5, 900µm Micron Pigtail Style Preconnectorized

Fiber Count	Indoor Riser	Indoor Plenum	Indoor/Outdoor Tight Buffered Distribution	Outdoor Dielectric	Outdoor Armored
12	F9G81B2GC60XXF	F9G82B2GC60XXF	F9G83B2GC60XXF	F9G84B2GC60XXF	F9G85B2GC60XXF

900µm Breakout

SC Connectors Standard.

Pulling eyes available to facilitate installation.

Call with Custom Requirements (ie. Installed in Innerduct)

Multimode 62.5, 900µm Micron Pigtail Style Preconnectorized

Fiber Count	Indoor Riser	Indoor Plenum	Indoor/Outdoor Tight Buffered Distribution	Outdoor Dielectric	Outdoor Armored
24	F9G91B2GC60XXF	F9G92B2GC60XXF	F9G93B2GC60XXF	Call for Information	Call for Information

900µm Breakout

SC Connectors Standard.

Pulling eyes available to facilitate installation.

Call with Custom Requirements (ie. Installed in Innerduct)

Multimode 62.5, 900µm Micron Pigtail Style Preconnectorized

Fiber Count	Indoor Riser	Indoor Plenum	Indoor/Outdoor Tight Buffered Distribution	Outdoor Dielectric	Outdoor Armored
36	F9GB1B2GC60XXF	F9GB2B2GC60XXF	F9GB3B2GC60XXF	Call for Information	Call for Information

900µm Breakout

SC Connectors Standard.

Call for other connector types.

Pulling eyes available to facilitate installation.

Call with Custom Requirements (ie. Installed in Innerduct)

Multimode 62.5, 900µm Micron Pigtail Style Preconnectorized

Fiber Count	Indoor Riser	Indoor Plenum	Indoor/Outdoor Tight Buffered Distribution	Outdoor Dielectric	Outdoor Armored
48	F9GC1B2GC60XXF	F9GC2B2GC60XXF	Call for Information	Call for Information	Call for Information

900µm Breakout

SC Connectors Standard.

Pulling eyes available to facilitate installation.

Call with Custom Requirements (ie. Installed in Innerduct)

Multimode 62.5, 900µm Micron Pigtail Style Preconnectorized

Fiber Count	Indoor Riser	Indoor Plenum	Indoor/Outdoor Tight Buffered Distribution	Outdoor Dielectric	Outdoor Armored
72	F9GD1B2GC60XXF	F9GD2B2GC60XXF	Call for Information	Call for Information	Call for Information

900µm Breakout

SC Connectors Standard.

Pulling eyes available to facilitate installation.

Call with Custom Requirements (ie. Installed in Innerduct)

Multimode 62.5, 900µm Micron Pigtail Style Preconnectorized

Fiber Count	Indoor Riser	Indoor Plenum	Indoor/Outdoor Tight Buffered Distribution	Outdoor Dielectric	Outdoor Armored
96	96 Fiber is available. Please call your Fiberdyne Labs Representative for a Quote				

900µm Breakout

SC Connectors Standard.

Pulling eyes available to facilitate installation.

Call with Custom Requirements (ie. Installed in Innerduct)

Multimode 62.5, 900µm Micron Pigtail Style Preconnectorized

Fiber Count	Indoor Riser	Indoor Plenum	Indoor/Outdoor Tight Buffered Distribution	Outdoor Dielectric	Outdoor Armored
144	144 Fiber is available. Please call your Fiberdyne Labs Representative for a Quote				

900µm Breakout

SC Connectors Standard.

Pulling eyes available to facilitate installation.

Call with Custom Requirements (ie. Installed in Innerduct)