

QSFP+

QSFP+ Transceivers

Type	Form Factor	Wave Length	Data Rate	Max Distance	Connectivity	TX Min (dBm)	TX Max (dBm)	RX Sensitivity	RX Overload	Length Budget
40G QSFP+ (4x10)	FDN-QSFP-SR4-10-01	850	41.25	100m	MM	-7.6	-1	-9.5	5	2
	FDN-QSFP-CSR4-10-01	850	41.25	300m	MM	-7.3	0	-9.9	0	2.4
	FDN-QSFP-IR4-10-01	1270-1330	41.25	2km	SM	-10	2.3	-13.7	2.3	4
	FDN-QSFP-LR4-10-01	1270-1330	41.25	10km	SM	-7	2.3	-11.5	2.3	4.5
	FDN-QSFP-PLRM-10-01	1270-1330	41.25	10km	SM	-7	2.3	-11.5	2.3	4.5
100G QSFP+ (4x28)	FDN-QSFP-28-SR4-10-01	850	103.1-111.8	100m	MM	-9.1	2.4	-11	2.4	1.9
	FDN-QSFP-28-LR4-10-01	1290-1310	103.1-111.8	10km	SM	-2.7	2.9	-21.1	2.5	18.4

* MSA/Cisco® IOS Compatible Model

Call [800-894-9694](tel:800-894-9694) or email us at sales@fiberdyne.com for other available brand optics.

Temperature rating is (0°C-70°C)

Extended or Industrial Temperature ratings are available upon request.