

Custom Labeling Available

Other Connector Combinations Available

Boot Options:

- Short Boots
- Bendable Boots
- *45° Boots
- *90° Boots
- Uni-Boots available for LCs

LC & SC connectors available with or without duplex clips/yokes

Plenum cable available upon request

[2 & 3mm cables available](#)

***Not available on all boots**



Singlemode Duplex 1.6mm Riser (Non-Plenum) SC Yoked to LC Clipped

Cable & Connector Specifications:	
Fiber Type	Singlemode OS2 (SMF-28)
Insertion Loss Per Connector	< 0.3dB, Typical 0.25dB
Return Loss VS. Polish Type	UPC: > 50dB, Typical 55dB APC: > 60dB, Typical 65dB
Apex Offset	< 50µm
Fiber Height	< 100nm
Repeatability	> 500 Cycles
Operating Temperature	-40°C To +75°C
Humidity Range	5% To 95% (Non-Condensing)
Strain Relief Boot Lengths	2.2cm to 3.5cm Available

Singlemode Duplex OS2 1.6mm Riser (Non-Plenum) Cables		
LC/UPC-LC/UPC	F9C21A3GCCXXXM	Specify Length When Ordering
LC/UPC-SC/UPC	F9C21A3GCCYXXXM	Specify Length When Ordering
LC/UPC-ST/UPC	F9C21A3GCC1XXXM	Specify Length When Ordering
LC/UPC-SC/APC	F9C21A3GCCWXXXM	Specify Length When Ordering
LC/UPC-FC/APC	F9C21A3GCCAXXXM	Specify Length When Ordering
LC/APC-LC/APC	F9C21A3GCFXXXM	Specify Length When Ordering
LC/APC-LC/UPC	F9C21A3GCFXXXM	Specify Length When Ordering
LC/APC-SC/UPC	F9C21A3GCFYXXXM	Specify Length When Ordering
LC/APC-SC/APC	F9C21A3GCFWXXXM	Specify Length When Ordering
SC/UPC-SC/UPC	F9C21A3GCYXXXM	Specify Length When Ordering
SC/UPC-SC/APC	F9C21A3GCYWXXXM	Specify Length When Ordering
SC/APC-SC/APC	F9C21A3GCWWXXXM	Specify Length When Ordering