

Custom Labeling Available

Other Connector Combinations Available

Boot Options:

- Short boots
- Bendable Boots
- \*45° Boots
- \*90° Boots

Plenum cable available upon request

[3mm cables available](#)

**\*Not available on all boots**



Singlemode Simplex OS2 2.0mm LC/UPC-LC/APC

Cable & Connector Specifications:	
Fiber Type	Singlemode OS2(SMF-28)
Insertion Loss Per Connector	< 0.3dB, Typical 0.25dB
Return Loss VS. Polish Type	UPC: > 50dB, Typical 55dB APC: > 60dB, Typical 65dB
Apex Offset	< 50µm
Fiber Height	< 100nm
Repeatability	> 500 Cycles
Operating Temperature	-40°C To +75°C
Humidity Range	5% To 95% (Non-Condensing)
Strain Relief Boot Lengths	2.2cm to 3.5cm Available

Singlemode Simplex OS2 2.0mm Riser Cables		
<b>LC/UPC-LC/UPC</b>	F9C11A2GCLLXXXM	Specify Length When Ordering
<b>LC/UPC-SC/UPC</b>	F9C11A2GCL6XXXM	Specify Length When Ordering
<b>LC/UPC-ST/UPC</b>	F9C11A2GCL1XXXM	Specify Length When Ordering
<b>LC/UPC-SC/APC</b>	F9C11A2GCLBXXXM	Specify Length When Ordering
<b>LC/UPC-FC/APC</b>	F9C11A2GCLAXXXM	Specify Length When Ordering
<b>LC/APC-LC/APC</b>	F9C11A2GCNNXXXM	Specify Length When Ordering
<b>LC/APC-LC/UPC</b>	F9C11A2GCNLXXXM	Specify Length When Ordering
<b>LC/APC-SC/UPC</b>	F9C11A2GCN6XXXM	Specify Length When Ordering
<b>LC/APC-SC/APC</b>	F9C11A2GCNBXXXM	Specify Length When Ordering
<b>SC/UPC-SC/UPC</b>	F9C11A2GC66XXXM	Specify Length When Ordering
<b>SC/UPC-SC/APC</b>	F9C11A2GC6BXXXM	Specify Length When Ordering
<b>SC/APC-SC/APC</b>	F9C11A2GCBBXXXM	Specify Length When Ordering